



Safety Data Sheet:
**Material Name: Elmer's
Repositionable Mounting
Spray Adhesive**
SDS ID: SDS-29
Issue Date: 2015-04-20
Revision: 1.1

Other Sections

[01](#) [02](#) [03](#) [04](#) [05](#) [06](#) [07](#) [08](#) [09](#) [10](#) [11](#) [12](#) [13](#) [14](#) [15](#) [16](#)

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

Elmer's Repositionable Mounting Spray Adhesive

Synonyms

E454

Chemical Family

Adhesive.

Product Use

Adhesive.

Restrictions on Use

None known.

Manufacturer Information

Elmer's Products, Inc
460 Polaris Parkway, Suite 500
Westerville, OH 43082
USA
Phone: 1-888-435-6377
Fax: 1-800-741-6046
Email: comments@elmers.com

Emergency Phone Number:

Poison Control Center
1-888-516-2502

For additional product information, access our website at www.elmers.com. To place an order, call 1-800-848-9400.

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable Aerosols - Category 1

Aspiration Hazard - Category 1

Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Eye Irritation - Category 2A

Specific Target Organ Toxicity - Single Exposure - Category 3 (respiratory system)

Hazardous to the Aquatic Environment - Acute - Category 2

Hazardous to the Aquatic Environment - Chronic - Category 2

GHS Label Elements

Symbol(s)



Signal Word

Danger

Hazard Statement(s)

Extremely flammable aerosol

May be fatal if swallowed and enters airways

Causes skin irritation

Causes serious eye irritation

May cause respiratory irritation. May cause drowsiness or dizziness

Toxic to aquatic life with long lasting effects

Precautionary Statement(s)

Prevention

Keep away from heat/sparks/open flame/hot surfaces - No smoking

Pressurized container: Do not pierce or burn, even after use

Do not spray on an open flame or other ignition sources

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapours/spray

Wash thoroughly after handling

Avoid release to the environment

Response

Collect spillage

IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

IF SWALLOWED: Immediately call a POISON CENTER/doctor

Do NOT induce vomiting

Specific treatment (see label)

Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
107-83-5	Isohexane	10-20
67-64-1	Acetone	10-20
115-10-6	Dimethyl ether	10-20
75-83-2	Neohexane	2.5-10
79-29-8	2,3-Dimethylbutane	2.5-10
106-97-8	Butane	2.5-10
74-98-6	Propane	2.5-10
96-14-0	3-Methylpentane	2.5-10

Section 4 - FIRST AID MEASURES

Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Skin

Wash with plenty of soap and water. If skin irritation occurs, get medical advice/attention. Remove contaminated clothing and wash it before reuse.

Eyes

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops or persists.

Ingestion

Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. If vomiting occurs, keep head lower than hips to help prevent aspiration. Aspiration into the lungs may result in pulmonary edema and pneumonitis.

Most Important Symptoms/Effects**Acute**

May cause respiratory irritation, eye irritation, skin irritation.

Delayed

No information on significant adverse effects.

Note to Physicians

Mineral oil, vegetable oil, or petroleum jelly may help soften the bonding between skin surfaces.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media**Suitable Extinguishing Media**

Dry chemical, foam or carbon dioxide.

Unsuitable Extinguishing Media

None known.

Special Hazards Arising from the Chemical

Contains gas under pressure, may explode when heated.

Special Protective Equipment and Precautions for Firefighters

Wear self-contained breathing apparatus with a full facepiece and protective clothing.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Damaged cylinders should be handled only by specialists. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire

burn. In case of fire and/or explosion do not breathe fumes. Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas. Wear personal protective clothing and equipment, see Section 8. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and Materials for Containment and Cleaning Up

Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering. Stay upwind and keep out of low areas. Eliminate all sources of ignition. Stop leak if possible without personal risk. Move containers away from spill to a safe area. Isolate area until gas has dispersed. Collect spillage. Prevent entry into waterways, sewers, basements, or confined areas.

Environmental Precautions

Avoid release to the environment. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Pressurized container: Do not pierce or burn, even after use. Do not spray on naked flames or any incandescent material. Do not eat, drink, or smoke when using this product. Do not puncture container. Do not cut, puncture, or weld on or near this container. Ground any equipment used in handling. Keep away from heat, sparks and flame. Do not reuse containers. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes. Avoid repeated or prolonged contact. Use only in well-ventilated areas. Wash hands thoroughly after handling. Do not empty into drains.

Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Keep away from incompatible materials. Keep away from heat, sparks and flame. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. This material can accumulate static charge by flow or agitation and can be ignited by static discharge. Keep out of reach of children.

Incompatible Materials

Oxidizing agents.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Acetone	67-64-1
ACGIH:	250 ppm TWA
	500 ppm STEL
NIOSH:	250 ppm TWA; 590 mg/m ³ TWA
	2500 ppm IDLH (10% LEL)
Europe:	500 ppm TWA; 1210 mg/m ³ TWA
OSHA (US):	1000 ppm TWA; 2400 mg/m ³ TWA
Mexico:	1000 ppm TWA LMPE-PPT; 2400 mg/m ³ TWA LMPE-PPT
	1260 ppm STEL [LMPE-CT]; 3000 mg/m ³ STEL [LMPE-CT]
Dimethyl ether	115-10-6
Europe:	1000 ppm TWA; 1920 mg/m ³ TWA
Butane	106-97-8
ACGIH:	1000 ppm STEL
NIOSH:	800 ppm TWA; 1900 mg/m ³ TWA
Mexico:	800 ppm TWA LMPE-PPT; 1900 mg/m ³ TWA LMPE-PPT
Propane	74-98-6
ACGIH:	(See Appendix F: Minimal Oxygen Content)
NIOSH:	1000 ppm TWA; 1800 mg/m ³ TWA
	2100 ppm IDLH (10% LEL)
OSHA (US):	1000 ppm TWA; 1800 mg/m ³ TWA

Biological limit value

There are no biological limit values for any of this product's components.

Engineering Controls

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear safety glasses with side shields. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin Protection

Wear appropriate chemical resistant clothing.

Respiratory Protection

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Glove Recommendations

Wear appropriate chemical resistant gloves.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	white liquid	Physical State	aerosol
Odor	Not available	Color	Not available
Odor Threshold	Not available	pH	Not available
Melting Point	Not available	Boiling Point	Not available
Freezing point	Not available	Evaporation Rate	Not available
Boiling Point Range	-44 to 150 °F	Flammability (solid, gas)	Not available
Autoignition	Not available	Flash Point	Not available
Lower Explosive Limit	Not available	Decomposition	Not available
Upper Explosive Limit	Not available	Vapor Pressure	Not available
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	0.6999
Water Solubility	Not available	Partition coefficient: n-octanol/water	Not available
Viscosity	Not available	Solubility (Other)	Not available
Density	Not available		

Section 10 - STABILITY AND REACTIVITY

Reactivity

No hazard expected.

Chemical Stability

Stable under normal conditions of use.

Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition.

Incompatible Materials

oxidizing agents.

Hazardous decomposition products

oxides of carbon, hydrocarbons.

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

May be fatal if swallowed. Prolonged exposure can cause nausea, dizziness, headache, and narcotic effects. May cause respiratory irritation. May cause drowsiness or dizziness.

Skin Contact

Causes skin irritation.

Eye Contact

Causes serious eye irritation.

Ingestion

May be fatal if swallowed and enters airways.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Acetone (67-64-1)

Oral LD50 Rat 5800 mg/kg

Inhalation LC50 Rat 50100 mg/m³ 8 h

Dimethyl ether (115-10-6)

Inhalation LC50 Rat 308.5 mg/L 4 h

Butane (106-97-8)

Inhalation LC50 Rat 658 g/m³ 4 h

Propane (74-98-6)

Inhalation LC50 Rat 658 mg/L 4 h

Immediate Effects

Causes skin irritation. Causes serious eye irritation. May cause drowsiness and dizziness.

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity Data

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.

Respiratory Sensitization

No information available for the product.

Dermal Sensitization

No information available for the product.

Component Carcinogenicity

Acetone	67-64-1
ACGIH:	A4 - Not Classifiable as a Human Carcinogen

Germ Cell Mutagenicity

No information available for the product.

Reproductive Toxicity

No information available for the product.

Specific Target Organ Toxicity - Single Exposure

respiratory system

Specific Target Organ Toxicity - Repeated Exposure

No target organs identified

Aspiration hazard

Aspiration Hazard. May be fatal if swallowed and enters airways.

Medical Conditions Aggravated by Exposure

No information available for the product.

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

Acetone	67-64-1
Fish:	

	LC50 96 h Oncorhynchus mykiss 4.74 - 6.33 mL/L; LC50 96 h Pimephales promelas 6210 - 8120 mg/L [static]; LC50 96 h Lepomis macrochirus 8300 mg/L
Invertebrate:	EC50 48 h Daphnia magna 10294 - 17704 mg/L [static] EPA; EC50 48 h Daphnia magna 12600 - 12700 mg/L IUCLID

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with all applicable regulations. Do not puncture container.

Section 14 - TRANSPORT INFORMATION

US DOT Information:

Shipping Name:AEROSOLS, FLAMMABLE

Hazard Class: 2.1

UN/NA #: UN1950

Packing Group: Not Available

Required Label(s): 2.1

IATA Information:

Shipping Name:AEROSOLS, FLAMMABLE

Hazard Class: 2.1

UN#: UN1950

Packing Group: Not Available

Required Label(s): 2.1

TDG Information:

Shipping Name:AEROSOLS

Hazard Class: 2.1

UN#: UN1950

Packing Group: Not Available

Required Label(s): 2.1

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Acetone	67-64-1
CERCLA:	5000 lb final RQ; 2270 kg final RQ

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: Yes **Chronic Health:** Yes **Fire:** Yes **Pressure:** Yes **Reactivity:** No

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
2-Methylpentane	107-83-5	No	Yes	Yes	Yes	Yes
Acetone	67-64-1	Yes	Yes	Yes	Yes	Yes
Dimethyl ether	115-10-6	No	Yes	Yes	Yes	Yes
2,2-Dimethylbutane	75-83-2	No	Yes	No	Yes	Yes
2,3-Dimethylbutane	79-29-8	No	Yes	No	Yes	Yes
Butane	106-97-8	Yes	Yes	Yes	Yes	Yes
Propane	74-98-6	No	Yes	Yes	Yes	Yes
3-Methylpentane	96-14-0	No	Yes	No	No	Yes

Not listed under California Proposition 65**Canadian WHMIS Ingredient Disclosure List (IDL)**

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

2-Methylpentane	107-83-5
	1 %
Acetone	67-64-1
	1 %
2,2-Dimethylbutane	75-83-2
	1 %
2,3-Dimethylbutane	79-29-8
	1 %
Butane	106-97-8
	1 %

Component Analysis - Inventory

2-Methylpentane (107-83-5)

US	CA	EU	AU	PH						CN	NZ	MX
----	----	----	----	----	--	--	--	--	--	----	----	----

					JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA			
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Acetone (67-64-1)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Dimethyl ether (115-10-6)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

2,2-Dimethylbutane (75-83-2)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

2,3-Dimethylbutane (79-29-8)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Butane (106-97-8)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Propane (74-98-6)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

3-Methylpentane (96-14-0)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Section 16 - OTHER INFORMATION

HMIS Rating

Health: 2 Fire: 4 Reactivity: 1

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

Summary of Changes

Updated SDS: 4/2/2015

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

Other Information

Disclaimer:

Supplier gives no warranty whatsoever, including the warranties of merchantability or of fitness for a particular purpose. Any product purchased is sold on the assumption the purchaser shall determine the quality and suitability of the product. Supplier expressly disclaims any and all liability for incidental, consequential or any other damages arising out of the use or misuse of this product. No information provided shall be deemed to be a recommendation to use any product in conflict with any existing patent rights.